DO PROBE SENSOR



FEATURES & BENEFITS

- Optical technology without calibration
- Real-time DO measurement
- Operator friendly, low maintenance design
- Range for wastewater to high purity applications
- Robust, compact and ultra-low power
- Stainless steel or titanium options available

OVERVIEW

Real Tech's dissolved oxygen (DO) sensor provides rapid real-time measurement of DO in water or wastewater. The sensor uses a luminescent optical technology approved by the ASTM International Method D888-05. The compact and robust sensor requires no calibration and very minimal power. Without oxygen consumption, the sensor allows for accurate measurement in many applications, especially those with very low oxygen concentrations.

MODELS

PRODUCT #	NAME	DESCRIPTION
DO1000	Real DO Probe Sensor	0-20 mg/L , 0-20 ppm or 0-200 % saturation

Includes sensor, 50 ft communication cable, and manifold (unless purchased with pole mounting kit). Controller and automatic cleaning system sold separately.





SPECIFICATIONS

CHARACTERISTIC	TECHNICAL DATA	
Model #	DO1000	
Measurement Principle	Optical measurement by luminescence	
Measurement Ranges	0-20 mg/L 0-20 ppm 0-200 %	
Resolution	0.01	
Accuracy	+/- 0.1 mg/L +/- 0.1 ppm +/- 1%	
Response Time	<5s	
Temperature Compensation	NTC thermistor	
Dimensions	Diameter: 25 mm, Length (not including cable): 146 mm	
Materials	Stainless steel 316L or Titanium	
Enclosure	IP68	
Maximum Pressure	70 PSI	
Electrical/Communication	From controller	
Storage Temperature	-10°C to 60°C (14 to 140°F)	
Weight	1 lb Stainless steel version	
Warranty	2-year limited warranty	

 $[\]hbox{*Technical Specifications are subject to change without notice.}$



